

TO GET YOUR NETWORK CONNECTED



1.6/5.6 Male Straight Crimp
Part No: E30600CR/**



1.6/5.6 Male Straight Clamp
Part No: E30600/CL/**



1.6/5.6 Male Right Angle Crimp
Part No: E30900CR/**



1.6/5.6 Male Right Angle Clamp
Part No: E30900CL/**



1.6/5.6 Male Bulkhead Solder
Part No: E30600BS



1.6/5.6 Male Right Angle PCB
Part No: E30900PCB

Application

The EQL 1.6/5.6 Series of Coaxial Connectors are used for digital transmission as well as other applications. It is available in a range of coaxial cable types including BT3002, BT2003, RG179, 2.5C-2V, 3C-2V, RG59 Bulkhead Panel Mount and PCB mounts.

Electrical Characteristics

Parameter	Typical Performance
Impedance	75 ohm
Frequency Range	DC-1GHz
Reflection Coefficient	<0.1 @ 1GHz
Voltage Rating	500 V peak/50 Hz max
Contact Resistance Centre Contact	< 4 mOhm
Contact Resistance Outer Contact	< 2 mOhm
Insulation resistance	> 10 Gohm
Temperature	Up to plus 100 °C

Material Specifications

Connector Part	Material	Finish
Body	Brass	Nickel
Inner Contact Male	Brass	Gold
Inner Contact Female	Phosphor Bronze	Gold
Outer Contact	Brass	Gold
Spring Loaded Contact	Phosphor Bronze	Gold
Insulator	Teflon	White
Crimp Ferrule	Brass	Nickel

Physical Characteristics

Parameter	Typical Performance
Engagement Force	10N
Mating Cycle	>500

** Coaxial Cable Type

Note: Specifications subject to change without notice.

EQL Telecommunications
Unit 20, 13 Swaffham Road
Minto NSW 2566
Australia

Postal Address:
P.O.Box 351
Minto NSW 2566
Australia

Tel: +61 2 9824 5680
Fax: +61 2 9824 5685
Email: sales@eql.com.au
Web: www.eql.com.au

ABN: 93 098 402 218