

TO GET YOUR NETWORK CONNECTED



M4 Straight Male Crimp (Plug)
Part No: E40850CR/**



M4 Straight Female Crimp (Jack)
Part No: E40860CR/**



M4 Straight Male (Plug)
Bulkhead Solder
Part No: E40850BS



M4 Straight Female (Jack)
Bulkhead Solder
Part No: E40860BS

EQL Telecommunications
Unit 20, 13 Swaffham Road
Minto NSW 2566
Australia

Postal Address:
P.O.Box 351
Minto NSW 2566
Australia

Tel: +61 2 9824 5680
Fax: +61 2 9824 5685
Email: sales@eql.com.au
Web: www.eql.com.au

ABN: 93 098 402 218

Application

The EQL M4 Coaxial Connectors are used for digital transmission as well as other applications. It is available in a range of coaxial cable types including BT3002, BT2003, RG179, 2.5C-2V, 3C-2V, RG59 and Bulkhead.

Electrical Characteristics

Parameter	Typical Performance
Impedance	75 ohm
Frequency Range	DC-1GHz
VSWR	1.3 max
Voltage Rating	250 V rms max
Dielectric withstand voltage	500 V rms min
Contact Resistance	2 m ohm
Insulation resistance	1000 M ohm Min
Temperature	Up to plus 100 °C

Material Specifications

Connector Part	Material	Finish
Body Male	Brass	Gold
Body Female	Brass	Nickel
Ferrule	Brass	Nickel
Muster Nut Female	Brass	Nickel
Insulator	Teflon	
Center Pin	Brass	Gold
Center Contact Female	Phosphor Bronze	Gold
Inner Contact Female	Phosphor Bronze	Gold

Physical Characteristics

Parameter	Typical Performance
Engagement Force	10 N Max
Cable Retention	~ 60 N Cable Specific
Contact Retention	> 5N

** Coaxial Cable Type

Note: Specifications subject to change without notice.